



NANYANG GOODWAY MACHINERY & EQUIPMENT CO., LTD.

Factory Add: ERLANGMIAO STREET, ERLANGMIAO TOWN, FANGCHENG COUNTY, HENAN PROVINCE, P.R.CHINA

GOODWAY 固德威 Website: www.cassavamachine.cn www.goodway.top

Cassava Peeling and Washing Machine



Processing Capacity: 4-6Tons/hour

Product Introduction: Cassava processing machine, cassava washing machine, cassava cleaning machine, cassava peeling machine, cassava washing and peeling machine for cassava starch and flour processing

Product Features of Cassava Peeling and Washing Machine

1. Solid and durable with all parts of the body including all food contact areas made of 304 stainless steel;
2. Operate safety with feed port outside the working area;
3. Continuous working with screw type feeding structure;
4. Adjust discharging speed to realize the best peeling effect with variable frequency motor;
5. Easy cleaning with all parts of the frame body made of 304 stainless steel;
6. With compact structure and beautiful appearance, very popular and acceptable in cassava processing field.



**NANYANG GOODWAY MACHINERY &
EQUIPMENT CO., LTD.**

Factory Add: ERLANGMIAO STREET, ERLANGMIAO TOWN, FANGCHENG COUNTY,
HENAN PROVINCE, P.R.CHINA

GOODWAY 固德威 Website: www.cassavamachine.cn www.goodway.top

Product Composition of Cassava Peeling and Washing Machine

1. Mainly consist of motor, transmission and rotary brush, there are two kinds of brush: hard or soft one according to the materials being processed, the structure design can avoid over damaging of materials.
2. With two motors, one for driving the brush roller with rotary brush to remove the pieces of peel from the raw materials without any broken, another one for driving the central axis with counter vane to guide the peeled materials from the feed port to the discharge port, meanwhile along with water coming out of shower pipe and get the materials wet, make them more easier for peeling and washing.

Technical Parameters of Cassava Peeling and Washing Machine :

Model No.	GD-BP-2000
Capacity	4-6Tons/Hour
Voltage	380V/50Hz 3Phase
Power	3.0KW
Rotate Speed	160-500R/Min
Inner Diameter of Rotary Drum	800mm
Inner Length of Rotary Drum	2000mm
Weight	450KG
Dimension(L ×W ×H)	2850×1200×1120mm